WY 380-3N V2 WY 400-3N V2

UHF Base Station 3 Elements Yagi Antennas 380-470 MHz

MAIN FEATURES

- Directional Wideband Yagi antennas
- Developped to provide a highly symmetrical radiation pattern in E/H-plane
- Computer-designed for high gain and excellent front-to-back ratio
- Anodized aluminium and stainless steel hardware
- Fully designed & Manufactured in Italy


UP GRADED FEATURES


- Fully sealed, IP67 waterproof
- New internal design to maximize Power handling




Electrical Data	WY 380-3N	WY 400-3N
Type	3 elements Yagi	
Frequency Range @ SWR ≤ 1.5	380 - 440 MHz	400 - 470 MHz
Impedance	50 Ω	
Radiation (H-plane) beamwidth @ -3 dB	125° - HCM code = 062LA14	
Radiation (E-plane) beamwidth @ -3 dB	65° - HCM code = 032EA14	
Front to back ratio	≥ 17 dB	
Polarization	Linear Vertical or Horizontal	
Gain	4.85 dBd - 7 dBi	
Max Power (CW) @ 30°C	160 Watts	
Grounding Protection	All metal parts are DC-grounded, the inner conductor shows a DC short	
Connector	N-female with rubber protection cap	

Mechanical Data		
Materials	Anodized 6063-T5 Aluminium, EPDM rubber, thermoplastic UV stabilized, Chromed Brass	
Wind Load @ 150 km/h	65 N	63 N
Wind Resistance	180 Km/h; 112 mi/h	180 Km/h; 112 mi/h
Wind Surface	0.048 m^2; 0.51 ft^2	0.047 m^2; 0.50 ft^2
Dimensions W x H (approx.)	565 x 400 mm; 1.9 x 1.3 ft	525 x 375 mm; 1.7 x 1.2 ft
Turning radius (approx.)	460 mm; 1.5 ft	420 mm; 1.4 ft
Weight (approx.)	1150 gr; 2.5 lb	1120 gr; 2.5 lb
Ingress Protection	IP 67	
Operating temperature	-40° C to +60° C	
Mounting Mast	∅ 35 - 60 mm; ∅ 1.4 - 2.4 in	
Boom / Dipole / Element Diameter	∅ 32 mm; 1.3 in / ∅ 24 mm; 0.95 in / ∅ 12 mm; 0.5 in	








SIRIO antenne


HI-QUALITY ANTENNAS MADE IN ITALY

MOUNTING INSTRUCTIONS

Correct mounting for horizontal polarization





		LR	L1	DR	D1
WY 380-3N	(mm)	396	276	132	106
	(in)	15.6	10.9	5.2	4.2
WY 400-3N	(mm)	371	260	124	100
	(in)	14.6	10.2	4.9	3.9




Correct mounting for vertical polarization


FT-6 Bracket Part list		
Pos	*Q.ty*	*Description*
1	1	Extruded aluminium bracket
2	2	Steel bracket
3	2	M8x216 U-bolt
4	4	M8 Grower washer
5	4	M8 Hexagonal nut
6	2	M6x20 Hexagonal head screw
7	2	M6 Grower washer
8	2	M6 Hexagonal nut
9	1	Connector Protection Cap
10	1	Plastic clamping band
Dimensions:		90x85x6 mm; 3.5x3.3x2.6 in
Weight:		550 gr, 1.2 lb
Re-order code: P/N 2519913.00		








Optional Tilting Bracket




Order p/n: 2519803.00
Materials & Hardware: zinc plated steel
Dimensions: 115 x 155 x 6 mm.
Weight: 800 gr

Part list	
Q.ty	*Description*
1	115x155x6 Tilting bracket
4	M8x25 Spheric head screw
4	M8 Grower washer
4	M8 Hexagonal nut




Stacking and Baying distance


WY380-3N: **L**=370mm;14.5in. **S**=530mm;20.8in
WY400-3N: **L**=350mm;13.8in. **S**=500mm;19.7in




Vertical polarization (Stacked)



Vertical polarization (Bayed)



Horizontal polarization (Bayed)



Horizontal polarization (Stacked)

HI-QUALITY ANTENNAS MADE IN ITALY

© Copyright **SIRIO antenne** - Technical Data are subjected to change - Printed in ITALY - Rev. 11/06/2026 - Cod. ID342