# SPO 118-2

## Sirio Professional Omni 2 dBi VHF Base Station Antenna 118-136 MHz

**DESCRIPTION: Wide band** omnidirectional base station antenna suitable for VHF AIR band service. The fiberglass protection radome and the anodized aluminium parts guarantee robustness and long life to all the SPO-antennas series. They are supplied with two strong extruded aluminium brackets and stainless steel hardware for a good installation on the mast.


#### **Electrical Data**


Туре	Dipole
Frequency Range	TX band 118-136 MHz @ SWR ≤ 1.5; Rx 108-136 MHz
Impedance	50 Ω
Radiation (H-plane)	360° Omnidirectional - HCM code = 000ND00
Radiation (E-plane)	Beamwidth @ -3dB = 78° - HCM code = 039ND00
Radiation angle deg.	0°
Polarization	Linear Vertical
Gain	0 dBd - 2.15 dBi
Max Power	100 Watts (CW) @ 30°C ambient
Grounding Protection	All metal parts are DC-grounded,
	inner conductor shows a DC short
Connector	N-female, with rubber protection cap

#### **Mechanical Data**

Materials	White fiberglass radome Ø 28.6 mm, anodized 6063-T5
	aluminium, brass, stainless steel, copper, EPDM rubber.
Wind Load at 150 km/h	56 N
Wind Resistance	180 Km/h; 112 mi/h
Wind Surface	0.048 m²; 0.51 ft
Operatin temperature	-40°C to + 80°C
Height (approx.)	1700 mm; 5.6 ft
Weight (approx.)	1400 gr; 3.1 lb
Ingress Protection	IP 67
Mounting Mast	Side mast with "V" bolt $\varnothing$ 35-60 mm: $\varnothing$ 1 4-2 4 in









### **MOUNTING INSTRUCTIONS**

